

Technical Data Sheet

SKYLT Original #5510



Application:

SKYLT is a water-based two-component product that can be applied to parquet, wooden, cork, concrete look and linoleum floors, among others, for normal to intensive use in houses, offices, shops and public buildings. It is also very suitable for furniture. It preserves the natural look of the substrate. Always apply a test coat first on unknown substrates. See the SKYLT INSTRUCTIONS for extensive application instructions and a legend of the symbols used. If you have specific questions, feel free to call us or send an app message to 06 – 47 05 78 24.

The values below apply to the ready product. Drying conditions of 20°C, 65% RH and sufficient ventilation are observed as applicable standard.

Colour	Pale white liquid, dries to clear transparent. Does not yellow.
Degree of gloss	Matt
Odour	Mild
Solids	32.5% BY VOLUME
pH	7.5
Consistency	Thin liquid
Ease of sanding	Easy
Coverage	8 - 12 m ² per litre
Dust dry	1 hour
Re-coatable	3 - 4 hours
Light use	12 hours
Intensive use	3 days (do not cover floor with film or carpets prior to this)
Scratch resistance	Very resistant to scratches from normal use, for instance sand under shoes.
Resistance to wear	Very good
Resistance	Very good chemical resistance to water, alcohol and detergents. Good resistance to coffee, wine and tea stains.

Technical Data Sheet

SKYLT Original #5510

Roughness/slip resistance	Prepared for daily use, for foot traffic.
Complies with	AgBB/DiBt – Germany Indoor Air Quality Decree – Belgium

Available in the following packaging(s):

0.5 litre can; item no. 5529471; EAN 8716544038097 (box = 6 x 0.5 ltr)

Part A = 0.47 ltr, part B = 0.03 ltr

1 litre bottle; item no. 5529473; EAN 8716544018730 (box = 12 x 1 ltr)

Part A = 0.94 ltr, part B = 0.06 ltr

4 litre can; item no. 5529474; EAN 8716544018747 (box = 4 x 4 ltr)

Part A = 3.76 ltr, part B = 0.24 ltr

See the MATERIAL SAFETY DATA SHEET for safe and healthy working conditions.