

ROYL

Maintenance Instructions ROYL Oil 1K #4550 / ROYL Oil 2K #4560 Clear, #4561 White, #4562 Black

With ROYL OIL-1K or ROYL OIL 2-K, your floor received a natural, sustainable and highly durable protective coat. Oiled surfaces are exceptionally easy to maintain. Of course, your floor does still need maintenance. After all, floors get subjected to a lot of strain. Regular and correct maintenance is essential. Luckily, this doesn't take too much time. This type of maintenance entails dry cleaning with a vacuum and/or wiper and moist cleaning with ROYL MILD CLEANER. The floor can be restored where necessary with ROYL MAINTENANCE OIL. You can also provide your floor with an extra protective coat by using ROYL FLOOR SOAP.

This is available in CLEAR and WHITE.

Note:

Never cover a recently oiled floor with plastic, rugs, etc.	Try to spare the floor as much as possible in the meantime.
Be careful when placing furniture.	After a week, you can place rugs.
Place mats at outside doors to prevent sand, dirt and moisture from ending up on the floor.	Provide chairs or other regularly moved furniture with felt furniture pads or wheels.
Only use ROYL maintenance products, so refrain from using green soap, all-purpose cleaners, ammonia, vinegar or other detergents. These detergents may damage your floor and/or cause discolouration.	Do not leave spilt substances.

Cleaning your oiled floor

- Vacuum, wipe or sweep the floor to remove sand and dirt as soon as possible (sand and dirt have a similar effect to sanding paper).
- Only lightly moisten your floor when cleaning. Always use a properly wrung-out mop. Use ROYL Mild Cleaner: or ROYL Floor Soap. Make sure to only use one of these products.

Note: The joints, seams and edges of a parquet floor are highly susceptible to water absorption. Use water sparingly to avoid discolouration and deterioration of the floor.

(Locally) restoring your oiled floor

- Over time, a used floor will deteriorate. ROYL Maintenance Oil can be used to (locally) restore your floor. For normal use, 1 or 2 times per year will suffice.
- Only apply oil to a clean surface. Make sure to clean the floor with ROYL Intensive Cleaner first. Major maintenance

The information provided through this document was carefully compiled and correct on the date of issue. Any changes will be published as part of newer versions without notice. No rights may be derived from the information in this document; The user should test the equipment for suitability for the intended application themselves.

Eventually, your floor may need a new, nourishing coat of ROYL OIL-1K or ROYL OIL 2-K. We recommend contacting your parquet installer for professional advice with regard to major maintenance.

	ROYL MAINTENANCE OIL #9090 #9080 water based	ROYL MILD CLEANER # 9110	ROYL FLOOR SOAP #9130 Clear #9131 White	ROYL INTENSIVE CLEANER #9120
Low-traffic floors, like living and bedrooms.	About 1x per year Local interim cleaning if necessary.	1x per week if necessary.	1x per week if necessary.	About 1x per year. Apply ROYL MAINTENANCE OIL afterwards.
Medium-traffic floors, like intensively-used living rooms, stairs and offices.	About 2x per year Local interim cleaning if necessary.	Multiple times per week if necessary.	Multiple times per week if necessary.	About 2x per year. Apply ROYL MAINTENANCE OIL afterwards.
High-traffic floors, like restaurants, schools and stores.	As often as necessary. Local interim cleaning.	Use when needed, daily if necessary.	Use when needed, daily if necessary.	As often as necessary. Apply ROYL MAINTENANCE OIL afterwards.

DAILY	USE	NOTES
Dry clean	Vacuum, wipe, sweep.	Sand and dirt have a similar effect to sandpaper.
WEEKLY		
Dry clean	Vacuum, wipe, sweep	Sand and dirt have a similar effect to sandpaper.
Moist cleaning	ROYL MILD CLEANER 50ml in 5L warm water. Use a faintly moist mop to mop the floor. Rinse regularly. ROYL FLOOR SOAP 50ml in 5L warm water. Use a faintly moist mop to mop the floor. Rinse regularly.	Only moisten the floor if necessary. Properly wring the mop. Only use ROYL MILD CLEANER or ROYL FLOOR SOAP.
Drying	Allow the surface to dry properly.	
YEARLY OR PERIODICAL		

The information provided through this document was carefully compiled and correct on the date of issue. Any changes will be published as part of newer versions without notice. No rights may be derived from the information in this document; The user should test the equipment for suitability for the intended application themselves.

MAINTENANCE		
Dry clean	Vacuum	Entire floor
Intensive cleaning	ROYL INTENSIVE CLEANER 200ml in 5L warm water. Use a faintly moist mop to mop the floor. Rinse regularly. Let soak for about fifteen minutes and remove the dissolved dirt with clean water. Regularly rinse the mop with clean water and wring out.	Use two buckets: one with soap and one with clean water to rinse the mop. Properly wring the mop.
Removing stains	Thoroughly clean with ROYL INTENSIVE CLEANER. Rub the stain with a scouring pad with LYNOTYN or pure GUM TURPENTINE. Apply ROYL MAINTENANCE OIL (for local touch-ups, see below).	Only apply if the stain cannot be removed through normal maintenance. In case of deep discolouration or stains, please consult your parquet installer.
Local touch-ups	Sprinkle ROYL MAINTENANCE OIL onto a scouring pad and thoroughly rub it into the surface. After applying the oil, dry the surface with a lint-free cotton cloth.	Oil should always be applied in very thin coats. The distributed oil should no longer stick or shine. Wet cloths covered in oil may spontaneously combust if not hung out to dry.
Drying	Allow the surface to dry properly.	An intensively cleaned surface should always be nourished with ROYL MAINTENANCE OIL afterwards.
Applying maintenance oil	Sprinkle ROYL MAINTENANCE OIL onto a scouring pad and thoroughly rub it into the surface. After applying the oil, spread it using a lint-free cotton cloth. Always hang cotton cloths and sponges out to dry before throwing them out.	Oil should be in the floor, not on the floor. Oil should always be applied in very thin coats. After drying, the surface should no longer stick or shine. Wet cloths covered in oil may spontaneously combust if not hung out to dry.
Renovation	A new coat of ROYL OIL-1K or ROYL OIL-2K. Preferably have this coat applied by your parquet installer.	



Note: due to a risk of spontaneous combustion due to heat generation, cloths, pads etc. that came into contact with oil or wax should be separately hung out to dry outside or wetted and placed in a properly sealed plastic bag.