




# ROYL ROYAL CLASS OIL

## SELECTION TABLE EXISTING FINISH & MAINTENANCE

<b>WATER-BASED MAINTENANCE OIL</b> #9080	<b>MAINTENANCE OIL</b> #9090 CLEAR #9091 WHITE	<b>ROYL OIL 1K</b> #4550 CLEAR	<b>ROYL OIL 2K</b> #4560 CLEAR #4561 WHITE #4562 BLACK	<b>ROYL PROJECT MAINTENANCE 2K</b> #4580 CLEAR	<b>ROYL ROLLABLE HARD WAX OIL</b> #4800 MATT #4850 SATIN
					
<b>QUICK AND EFFORTLESS LOCAL REFRESHING</b>	<b>TOPPING UP OF A THIN SURFACE</b> ALSO LOCALLY	<b>FOR PROFESSIONAL MAJOR MAINTENANCE</b>	<b>FOR PROFESSIONAL MAJOR MAINTENANCE</b>	<b>FOR PROFESSIONAL MAJOR MAINTENANCE</b>	<b>FORMS A SEALING FILM LAYER</b> EASY TO APPLY WITH A ROLLER <b>ALSO SUITABLE FOR PRIVATE INDIVIDUALS</b>
<b>IDEAL FOR THE PRIVATE INDIVIDUAL</b>	<b>UNIVERSALLY USABLE</b>	<b>MOST SUSTAINABLE CHOICE</b>	<b>MOISTURE RESISTANT AFTER 24 HOURS</b>	<b>PROJECT FLOORS AND DARKER TROPICAL HARDWOOD</b>	
<b>NOTE!</b>					
<b>Apply only to floors with an even colour. Not suitable on bare wood.</b>				<b>Apply only to floors with an even colour.</b>	<b>Apply only to floors with an even colour.</b>
<b>OIL %</b>					
Ultra-thin liquid. 15% oil. Not greasy.	Thin liquid, 30% oil. Greasy.	Liquid, 100% oil. Greasy.	Liquid, 100% oil. Greasy.	Viscous liquid, 100% oil. Greasy with wax.	Film-forming.
<b>ARBO (NL)</b>					
<b>Waterbased</b>	Solvent based.	<b>Solvent-free.</b>	<b>Solvent-free.</b>	<b>Solvent-free.</b>	Solvent based.
Complies with ARBO for professional indoor use.	Does not comply with ARBO for professional indoor use.	Complies with ARBO for professional indoor use.	Complies with ARBO for professional indoor use.	Complies with ARBO for professional indoor use.	Does not comply with ARBO for professional indoor use.
<b>COLOUR RESTORATION</b>					
Not suitable for colour restoration. Not suitable for deep scratches or bare wood.	Colour maintenance. Makes deeper scratches less visible.	Best colour restoration as exact same colour/mixing ratio possible. Makes deeper scratches less visible.	Best colour restoration as exact same colour/mixing ratio possible. Makes deeper scratches less visible.	Gives colour enhancement, effect varies by colours and floors. Makes deeper scratches less visible.	Not suitable for colour restoration
<b>APPLICABLE WITHOUT ADDITION OF COLOUR PIGMENT TO</b>					
All colours	<b>Clear:</b> all colours, with the exception of C10, C10+10, C30, W09, W10 en W27. <b>White:</b> C10, C10+10, C30, W09, W10 en W27.  On colours C11, W01, W14, W16, W17, W19, W20, W22, W23, W26 Clear or White are both possible. <b>Clear:</b> Least effect on the colour; <b>White:</b> Enhances white undertone.	Clear without colour pigment	<b>Clear:</b> on Clear without colour pigment  <b>White:</b> on White without colour pigment  <b>Black:</b> on Black without colour pigment	Clear without colour pigment	All colours
<b>ADDING COLOUR PIGMENT</b>					
Not possible	Colorable Max. half a poche	Colorable Max. 2 pouches	Colorable Basis Clear max. 2 pouches Basis White max .1 poche Basis Black max .1 poche	Colorable Max. 1 poche	Not possible
<b>STRENGTHENING OF THE COLOUR POSSIBLE</b>					
No	No	No	No	Yes	No
<b>APPLICABLE TO ROYL ROLLABLE HARD WAX OIL</b>					
No	<b>Clear</b> - Yes <b>White</b> - No	No	No	No	No
<b>HOE VAAK VOER JE HET ONDERHOUD UIT</b>					
<b>Mind the signals.</b>	<b>Mind the signals.</b>	<b>Mind the signals.</b> Standard: once every 2 years. The entire surface.	<b>Mind the signals.</b> Standard: once every 2 years. The entire surface.	<b>Mind the signals.</b> Standard: once every 2 years. The entire surface.	<b>Mind the signals.</b> Standard: once every 2 years. The entire surface.
<b>SIGNALS THAT MAINTENANCE OR TOP-UP IS NEEDED</b>					
<ul style="list-style-type: none"><li>Water drops and water rings immediately penetrate the wood and temporarily darkening it.</li><li>The floor becomes grubby, looks duller and shabbier, the wood grain turns grey.</li><li>A visible walkway is beginning to form.</li><li>A visible colour difference appears in front of the sofa or at the dining table.</li><li>The floor becomes more prone to staining. A drop of olive oil, piece of crisps or drop of soft drink will immediately leave a stain</li><li>Walking on the floor or moving chairs causes gloss disturbances.</li></ul> <div><b>TIP</b> Make your own drops on your floors to test water resistance from time to time.</div>					
<b>PRE-TREATMENT</b>					
Mopping with ROYL Mild Cleaner #9110. <b>If previously cleaned with ROYL Floor Soap #9130</b> , then mopping with ROYL Intensive Cleaner #9120.	Mopping with ROYL Intensive Cleaner #9120	Mechanical scrub cleaning With ROYL Intensive Cleaner #9120	Mechanical scrub cleaning with ROYL Intensive Cleaner #9120	<b>On Clear without COLOUR PIGMENTS:</b> Mechanical scrub cleaning with ROYL Intensive Cleaner #9120  <b>On oil with COLOUR PIGMENTS:</b> Mopping with ROYL Intensive Cleaner #9120.	<b>Maintenance coat over existing layer</b> <b>Rollable Hard Wax Oil:</b> Mopping with ROYL Intensive Cleaner #9120 and intermediate sanding P180. <b>First layer over existing ROYL 1K/2K:</b> Mopping with ROYL Intensive Cleaner, if necessary, matt with a purple pad.
<b>MANUAL (spot) MAINTENANCE TO 2M²</b> For larger surfaces, use a 1-disc buffing machine.					
Light in use. Quick and easy to wipe dry to the same colour and gloss level as the surrounding surface.	Rubbing in manually and rubbing dry to the same colour and gloss level as the surrounding surface is a tough job.	Rubbing in manually and rubbing dry to the same colour and gloss level as the surrounding surface is physically heavy.	Rubbing in manually and rubbing dry to the same colour and gloss level as the surrounding surface is physically heavy.	Rubbing in manually and rubbing dry to the same colour and gloss level as the surrounding surface is physically demanding.	Apply with roller. Local touch-up not possible.
<b>MACHINE MAINTENANCE FROM 2M²</b> Handle large surfaces in sections.					
Work in sections of max 10m² or within 15 minutes to prevent premature drying.	Work in sections of max 10m² or within 15 minutes to prevent premature drying.	Up to 60-80m² or to be finished within 2-3 hours in one go.	Up to 60-80m² or to be finished within 2-3 hours in go.	Up to 60-80m² or to be finished within 2-3 hours in go.	Apply with roller. Mechanical processing not possible.
<b>DRYING TIME/RESILIENT AFTER</b> Drying times apply at 20°C, 65% RH with sufficient ventilation. Drying times may vary at other conditions.					
Light load/walkable after > 6-12 hours. Same day possible under optimal drying conditions. Otherwise, allow overnight drying. Complete curing after 2-3 days.	Light load/walkable after >6-12 hours. Same day possible with optimum drying conditions. Otherwise maintain overnight drying. Full curing after 2-3 days.	Light load/walkable after >16-24 hours. At least allow overnight drying. Complete curing after appr 10-14 days.	Light load/walkable after >6-12 hours, preferably overnight. Moisture resistant after 24 hours. Complete curing after 5-7 days.	Light load/walkable after >6-12 hours, preferably overnight. Moisture resistant after 24 hours. Complete curing after 5-7 days.	Light load/walkable after >12 hours. Complete curing after 8-10 days. Drying time can increase significantly under less favourable drying conditions.



Using our **WhatsApp** number **+31 (0)6 47 05 78 24**, you can get instant advice and guidance from us on weekdays between 8am and 5pm. Send photos along and our advisers will look at them and call or app you with advice.