

ROYL Oil 1K #4550

Technical Data Sheet



Application:

Solvent-free, impregnating oil for parquet, furniture and other wooden surfaces. Suitable for intensively used surfaces.

View the ROYL MANUAL for extensive usage instructions and an explanation of the symbols.

Always test a small area on unknown surfaces. Feel free to call us or send a message to 06 - 47 05 78 24 if you have any specific questions.

The values below apply to the finished product. This information is based on standard drying conditions of 20 °C, a relative humidity of 65% and sufficient ventilation.

Finish	Matte
Odour	Mild
Solids content	About 100 vol%
VOC content	0 g/l
Yield	30 - 40 m ² per litre depending on the surface.
Moisture resistance	After 1 week
Lightly usable	24 - 48 hours
Fully usable	After 2 weeks (do not cover the floor with foil or carpets before this time)

Resistance	***
Roughness/anti-slip	Normal
Application	Do not use if the (floor) temperature is lower than +10°C or in case of a humidity of > 80%. Ensure sufficient ventilation while applying the oil and during drying.
Shelf life	In closed packaging, shelf life of at least 2 years. Limited shelf life after opening.

The technical specifications above apply to ROYL OIL - 1K Clear in standard conditions. Different colours may result in deviations.

Available in the following type(s) of packaging:

1-litre can; (box = 6x1 litre)

5-litre can;

Please view the SAFETY INFORMATION SHEET for health and safety information.